



FICHA RESUMEN PS-6509

FEATURES

- ATOM® Platform high performance 15" Panel PC
- Ultra slim Panel PC
- 15" LCD display with ELO 5-wire resistive or ELO surface capacitive touch screen
- Supports CF type I/II socket
- VESA 100 Wall mounting standard
- Optional MSR & Smart Card reader
- Ideal system to be floor-stand kiosk

SPECIFICATIONS

Systems

CPU Support Intel® ATOM® N270 1.6GHz
 Memory 1 x DDR2 SO-DIMM Slot, 512MB DDR2 SO-DIMM (up to 1GB MAX)
 Core Logic Intel® 945GSE & ICH7M support FSB 533, DDRII 533
 Network Giga Fast Ethernet (optional 802.11 b/g WLAN Mini-PCI module)
 Audio AC'97 Codec with internal mono speaker (1 x 2watt)
 Power Supply 120W Power adapter
 System Weight 6.5 kg
 Dimension (W x H x D) 365 x 318.5 x 77 mm (14.37" x 12.54" x 3.03")
 Mounting Type Support VESA 1000 standard
 O.S.Support Windows XP / XPE, Linux, WEPOS, POSReady 2009
 HDD 1 x 2.5" SATA HDD (standard 160GB)
 CF 1 x bootable Compact Flash slot for CF type I/II storage (optional)
 EMC & Safety CE, FCC, cUL

I/O Ports

USB 5 x USB 2.0 port (4 on I/O port, 1 on the side of the back cover)
 Serial Port 3 x DB-9 (COM 1/2/3), 1 x RJ45 (COM 4), +5/12V Selectable
 Keyboard & Mouse 2 x PS/2 port
 LAN 1 x Giga Fast Ethernet
 Audio 1 x Line-out, 1 x Mic-in Audio Jack
 VGA 1 x DB-15 VGA Interface

Display

LCD 15" TFT LCD
 Max. Resolution 1024 x 768
 Brightness 250 cd/m²
 Touch Screen 5 ~ wire analog resistive / Surface capacitive
 Viewing Angle 0 ~ 60 degree

Environment

Operation Temperature 0°~35°C(32°~95°F)
 Storage Temperature -20°~60°C(-4°~140°F)
 Humidity 20~90%

